

FARASTAR

PULSED FIELD ABLATION GENERATOR



Purpose-built, biphasic and bipolar waveform generator designed to deliver tailored PFA therapy through the FARAWAVE catheter



FARAPULSE



FRONT CONNECTION PANEL

Pre-production model shown

PACING CONTROL

Mode **Sync** Async

Cycle Length \downarrow 500 ms \uparrow
120 bpm

Channel 1 \downarrow 10 mA \uparrow
Disabled

Channel 2 \downarrow 10 mA \uparrow
Disabled

THERAPY CONTROL

End Procedure

VOLTAGE kV \leftarrow 1.8 1.9 2.0 \rightarrow

FARAWAVE connected

Cancel Therapy

System Ready

Deliver Energy

DELIVER

TOUCHSCREEN USER INTERFACE



REAR CONNECTION PANEL



POWER SUPPLY AND ACCESSORY STORAGE



Pre-production model shown



FARASTAR

ORDERING INFORMATION

REFERENCE NUMBER	
61M401	FARASTAR Pulsed Field Ablation Generator
SHIPPING INFORMATION	
WEIGHT	245 kg
DIMENSIONS	L 120 x H 82 x W 198 cm
TECHNICAL SPECIFICATIONS	
INPUT VOLTAGE	230V / 50Hz (EU)
OUTPUT VOLTAGE	1.8 - 2.0 kV, user-adjustable Proprietary FARAPULSE biphasic, bipolar waveform
WEIGHT	130 kg
DIMENSIONS	L 79 x W 61 x H 117 cm (160 cm with monitor)
USER INTERFACE	Articulating touchscreen
ACCESSORIES	
41M404	FARASTAR Catheter Connection cable
61M403	FARASTAR Stimulation Module
61M404	FARASTAR Stimulation Module Cable
61M405	FARASTAR EGM cable
<p>Contact your FARAPULSE representative for a full list of FARASTAR accessories</p>	

for more information contact:
eu.cs@farapulse.com

Rheinstr.45-46 | 12161 Berlin
 Phone +49 30 40 50 45 334
www.farapulse.com



FARAPULSE

Authorized Representative
 MedPass SAS
 95 bis Boulevard Pereire
 75017 Paris, France